

## Electrical characteristics

DATE SHEET-CP234044

Type CP234044

3.0V 650mAh

System lithium/ manganese dioxide

Nominal capacity (mAh) 650@1mA to 2.0V @23°C

Rated voltage (V) 3.0

Impedence at 1kHz ( $\Omega$ ) 5

Max. continuous current (mA) 200

Max. pulse current (mA) 500

Storage temperature -20 ~+40 °C

Operation temperature range -20°C ~+60°C

Weight (g) 7.0

Specific energy 280Wh/Kg


Energy density 480Wh/L

Anode tape/cathode tape Aluminum/Nickel

Self Discharge Rate Under 2% for years@30°C

Jacket Flexible Aluminum Foil Packaging

Max. dimensions (mm) 2.5×40.5×45



## Key Features

High Energy Density

- High single cell voltage
- Light weight
- Small Size
- High security
- Stable operating voltage
- Wide Operating temperature range
- Low Self-discharge rate
- Flexible on shape design
- Restricted for UL、UN38.3 and ROHS
- UL file: MH45782

Any special or specific for shape, thickness or discharge rate, please consult GMB.

Guangzhou Markyn Battery Co., Ltd.

Block 2, haijing Road 06, Markyns industrial Zone, Xinzao Town,  
Panyu District, Guangzhou, P.R.C..

Tel: (86)20 — 34729558 Fax:(86)20 — 3476 5531



Email:sales@gmbattery.com



**Discharge Curve****DATE SHEET- CP234044**

Constant Current

3.0V650mAh

**Capacity VS Temperature****Guangzhou Markyn Battery Co., Ltd.**

Block 2, haijing Road 06, Markyns industrial Zone, Xinzao Town,

Panyu District, Guangzhou, P.R.C..

Tel: (86)20 — 34729558 Fax: (86)20 — 3476 5531

Email: sales@gmbattery.com

